



DS priključni kabli ClassA++ (105dB) , WISI DS Connection cables Class A++ (105dB), WISI

TV in medijske storitve, ki temeljijo na IP, zahtevajo visoko kakovostne in zanesljive profesionalne kableske rešitve. Visoka oklopljenost priključnih koaksialnih kablov DS ... razreda A ++ (EN 50117), z najvišjimi mehanskimi in tehničnimi lastnostmi zagotavlja enostavno in učinkovito vgradnjo za multimedijška omrežja. Kabel Class A ++ varuje podatkovne tokove pred zunanji viri, kot so 4G ali LTE... S premerom kabla 5mm in polmer upogibanja 30 mm omogoča enostavno rokovanje. Na voljo v dolžinah 1,5m in na zahtevo 3,0 in 5,0 metrov.

IP-based TV and media services require high quality and reliable professional cable solutions. The highly shielded pre-assembled broadband coaxial cable DS... Class A++ screening with the highest mechanical and technical characteristics for easy and efficient installation in multimedia networks. This powerful Class A++ cable protects data streams perfectly against external sources such as 4G or LTE radio equipment. With a diameter of just 5mm and a bending radius of 30 mm it allows for easy handling by any installer. The cable has a tensile strength of more than 130 N and is further more equipped with Beryllium Copper connections making it extremely robust with superb line properties. Available in lengths of 1.5/3.0/5.0 meters.

Tipi DS priključnih kablov / Types of DS connection cables

Ravni konektorji/Straight connectors
DS 37U 0150_connection_cable IECf-IECm
DS 38U 0150_connection_cable Fm-Quick-IECf
DS 39U 0150_connection_cable Fm-Quick-IECm
DS 50U 0150_connection_cable 2XFm-Quick
1xkotni konektor/1x angled connector
DS 40U 0150_connection_cable Fm_Quick-FmQuick_angled
DS 46U 0300_connection_cable IECf-IECm_angled
DS 47U 0150_connection_cable IECm-IECf_angled
DS 48U 0150_connection_cable Fm_Quick-IECf_angled
DS 49U 0150_connection_cable IECm-Fm_Quick_angled



Color code / barvna legenda:

IECm = IECmale ; **blue ring / modri obroč**



IECf = IECfemale ; **green ring / zelen obroč**



Fm_Quick = Fmale_Quick ; **red ring / rdeč obroč**

