

WISI VX 57 A

Universal line amplifier, remote supplied



ELPAS



Description

At a glance:

- Two active outputs
- All settings with OH 41 A handset or LMT (laptop) when using a HMS-transponder
- Interface for NMS-function
- Diplex-filter module, splitter-/tap module pluggable
- Return channel amplifier pluggable
- ASC module VX 58

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 3. Juni 2015, 8:51 vorm.

Technical data

Downstream

Inputs	1 pcs.
Input measurement socket	20 dB
Input return loss	>20 dB
Frequency range downstream	47/85...1006 MHz
Gain downstream	2x 39,5 dB (with XM 51 A (4/4 dB))
Noise figure downstream	≤6,5 dB
attenuator downstream	0...15 dB (0,1 dB-steps)
equaliser downstream	0...15 dB (0,1 dB-steps)
interstage attenuator downstream	0/5/10 dB
interstage equalizer downstream	0/6/9 dB
Output level 1	2x 111 dB μ V (CENELEC 42 channels, flat, at CSO/CTB >60 dB)
Output level 2	2x 114 dB μ V (CENELEC 42 channels, 6 dB slope, at CSO/CTB >60 dB)
Output test point	20 dB
Output return loss	>20 dB
Output splitter	1 pcs.

Upstream

Frequency range upstream	5...30/65 MHz Depending on diplexers
Gain upstream	26 dB
noise figure upstream	≤10 dB
attenuator upstream input	0...30 dB
attenuator upstream output	0...30 dB
Equalizer US	0...10 dB
Output level 4	116 dB μ V
ICS, US	0/-8/-45 dB (switchable)
Return channel test point	20 dB

Connectors

PG11	4 pcs.
------	--------

General data

Operating voltage AC	27...65 V (50/60 Hz)
Power consumption	33/31 W (with/without transponder)
Remote power	<8 A
Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	261x215x100,4 mm
Operating temperature range	-20...+50 °C
Lightning protection	6 kV (EN61000-4-5, 1,2/50 μ s pulse)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	340 x 283 x 155 mm
	dm ³
Gross weight sales unit	3.500 kg
Shipping unit	pcs.

Packaging data

Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	15 dm ³
Gross weight shipping unit	3.5 kg
	cm
	N
EAN	4010056704230
Article number	70423
Customs tariff number	8543703000