

FTTH Box 12

Description

This Lockable IP54 distribution box offers the ability to terminate 24 fibres housed in a strong robust ABS+PC enclosure for indoor and outdoor applications. With the ability to use both SC simplex and LC duplex adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibres. In addition to the interchangeable adaptors the enclosure also offers up to 24 exit points for patching cables and 1 standard cable entry point for loose tube, tight buffer, pre-terminated and steel tape armoured cable. Each enclosure has integrated strength member tie positions and bend radius protection with the addition of a removable front door allowing for quick and easy installation.

Feature

- Up to 24 fibres
- Removable splice tray for easy installation
- Multiple adaptor options available
- 4 adaptor positions
- IP 54
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 24 exiting cables + 1 incoming cable
- Removable door for ease of installation
- ROHS compliant
- Supplied with 24 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps

Application

- Data centres, premise installations, telecommunication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Wall mounted, pole mounted, Indoor/outdoor applications

Specification

Dimension 225x195x65mm

Capacity 12 fibers/24 fibers

Adapter 12xSC simplex, 12xLC Duplex

Operation Temperature -40c~+60c

