

## VX 45 mali distribucijski ojačevalniki WISI VX 45 small distribution amplifiers WISI

VX 45 fleksibilni distribucijski ojačevalniki do 1GHz – ojačanje DS: 38dB, US: 30dB

VX 45 flexible **home distribution amplifier** with a frequency range up to 1 GHz - gain DS: 38dB, US: 30dB  
Vgrajen aktivni povratni pas / built-in return path

- Visok izhodni nivo / high output level 107 dB $\mu$ V
- 230V and 65V types
- Nastavitve z zveznim preklopnim stikalom / Alignment by uninterruptible rotary switch and jumper



	Tehnični podatki / technical data	
Tip / Type	VX 45D 3830	VX 45R 3830
Frekvenčno področje / Frequency range	5-65/85-1006 MHz	5-65/85-1006 MHz
Ojačanje / Gain DS	38 dB	38 dB
Attenuator	0-15 dB	0-15 dB
Korekcija / Equalizer	0-22,5 dB	0-22,5 dB
Interstage	0/6 dB	0/6 dB
Izhodni nivo / Output level		
Cenelec 42 CTB / CSO flat	107 dB $\mu$ V	107 dB $\mu$ V
Mer. Točka / Test socket dB	-20	-20
<b>Povratni pas / US return path</b>	5-65 MHz	5-65 MHz
Ojačanje pov. pas / Gain return path (2,5dB Jumper)	30 dB	30 dB
Attenuator	0-15 dB	0-15 dB
Interstage Equal. dB	0/3/6/9	0/3/6/9
Izhodni nivo / Output level max. IMA3 60 dB	118 dB $\mu$ V	118 dB $\mu$ V
Napajanje/Operating voltage	230 V	27-65V (1A)
Poraba / Power consumption	6 W	6 W
Dimenzije / Dimensions (WxHxD)	163 x 90 x 47 mm	